

Verschraubungsteile


Technische Anweisungen

Werkstoffe: Messing vernickelt
Aluminium

Dichtungen: NBR, ölbeständig

Höchstbetriebsdruck: 16 bar

Betriebstemperatur: -10°C bis +80°C



zylindrisches Gewinde




konisches Gewinde



zylindrisches Innengewinde

Baureihe S21

Einschraubtülle



| Typ | A | B | C | D | CH |
|--------|-----|----|------|----|----|
| S21086 | 1/8 | 6 | 29,5 | 6 | 12 |
| S21087 | 1/8 | 7 | 29,5 | 6 | 12 |
| S21088 | 1/8 | 8 | 29,5 | 6 | 12 |
| S21089 | 1/8 | 9 | 29,5 | 6 | 12 |
| S21081 | 1/8 | 10 | 30,5 | 6 | 12 |
| S21046 | 1/4 | 6 | 32 | 8 | 14 |
| S21047 | 1/4 | 7 | 31,5 | 8 | 14 |
| S21048 | 1/4 | 8 | 32,5 | 8 | 14 |
| S21049 | 1/4 | 9 | 32,5 | 8 | 14 |
| S21041 | 1/4 | 10 | 32,5 | 8 | 14 |
| S21042 | 1/4 | 12 | 32,5 | 8 | 14 |
| S21044 | 1/4 | 14 | 43 | 9 | 15 |
| S21038 | 3/8 | 8 | 34 | 9 | 19 |
| S21039 | 3/8 | 9 | 34 | 9 | 19 |
| S21031 | 3/8 | 10 | 34 | 9 | 19 |
| S21032 | 3/8 | 12 | 34 | 9 | 19 |
| S21034 | 3/8 | 14 | 34 | 9 | 19 |
| S21037 | 3/8 | 17 | 38,5 | 9 | 19 |
| S21022 | 1/2 | 12 | 36 | 10 | 22 |
| S21024 | 1/2 | 14 | 37,5 | 10 | 22 |
| S21027 | 1/2 | 17 | 39,5 | 10 | 22 |
| S21220 | 1/2 | 20 | 39,5 | 10 | 22 |
| S21718 | 3/4 | 18 | 41 | 11 | 30 |
| S21720 | 3/4 | 20 | 42 | 11 | 30 |